

## Liquid Rubber® HBS200

Liquid Rubber® HBS200 is a universal sealer with adhesion to almost every surface. It is a protective liquid coating that can be used for all kinds of applications. The quality is unequalled, the application easy and the protection is sustainable. The coating adheres e.g. on concrete, stone, metal, bitumen, EPDM (epdm primer), wood, PVC and zinc. This makes the coating ideal for waterproofing and air barrier applications of basements, roofs, gutters, outlets, window frame connection, ground level details, planters and many more.



## Liquid Rubber® Two-component series

The two componenten Liquid Rubber® series are liquid water-based coatings that are applied as a two-component system. The second component is a salt mixture which ensures a directly dried coating. After application the coating results in a seamless protective membrane with a high quality and high flexibility. A protective coating against penetration of water, salt or other chemicals.



# JointFiller

original product

## Liquid Rubber Europe

Groot Mijdrechtstraat 15

3641 RV Mijdrecht

The Netherlands

T +31(0)297 58 78 66

F +31(0)297 58 78 61

[info@liquidrubbereurope.com](mailto:info@liquidrubbereurope.com)

[www.liquidrubbereurope.com](http://www.liquidrubbereurope.com)

## Liquid Rubber® JointFiller

### Product characteristics

Liquid Rubber® JointFiller is an environmentally friendly water-based product without any solvents or VOC's. The product can be applied as a waterproofing or air barrier sealant and cures into a seamless flexible joint filling sealant.

#### The special characteristics:

- waterproof and air barrier.
- strong, seamless and fully adherent to the surface.
- applicable on light wet surfaces.
- effective for waterproofing.
- UV- and acid-resistant.
- sustainable.
- resistant against large temperature fluctuations (-40 °C to +160 °C).
- waterbased.
- **environmentally friendly** and contains no VOC's or other toxics.
- paintable.

### Applications

Liquid Rubber® JointFiller can be applied in many different situations. It can be used for waterproofing, air barrier and protection against corrosion. JointFiller adheres to concrete, wood, plastics, roofing and many more.

### Application

Liquid Rubber® JointFiller is a single component product and is applied by means of a silicon (tube) gun. The product can also be used in closed areas due of the odorless and **environmentally friendly** product features. During the application no extra body protection is required.

#### Important for application:

- the surface needs to be clean, dry and free of greas. Dust or other loose particles need to be removed.
- temperature (ambient and/or surface) needs to be above +5°C.
- the use of a primer, especially on a porous surface, is recommended for optimum adhesion.
- the product should not be exposed to (rain) water within 24 hours.

### Packaging & usage

Liquid Rubber® JointFiller is available in tubes of 310ml. The usage of the products is depending on the size of the joint.

**Important:** in case of a large joint filling the product must be applied in multiple layers. JointFiller can shrink up to 25%. Degrease the first layer before applying a new layer.

